

Cylindrical Knob Set



Model:

G 3860

SUS 304 Stainless Steel Knob

G 3861



Specification

- Exposed Trim: Wrought brass or stainless steel. Brass material available plated to match finishes indicated
- Keying: 5-pins tumble with three brass keys.
- 70mm diameter rose and mechanism adjustment for various door thickness
- Door Range: (35mm to 45mm) Standard
- Backset: (60mm) as standard backset, (70mm) backset available.


Features

- Completely left hand and right hand door reversible
- Two piece knob for better security
- Wrought steel cylindrical lock housing with chromated finish for better corrosion resistance

Finishing

- M11** - Antique Copper (Entrance Only)
- M26D** - Satin Chrome

Diagram




G 3861



Entrance/Office Lock

Both knobs locked or unlocked by key outside or push button inside.


G 3866



Classroom Lock

Outside locked or unlocked by key outside. Inside always free providing emergency exit.


G 3862



Privacy Lock

Latch bolt operated by knob from either side knob is locked by push button inside and unlocked by emergency release outside, rotating inside knob or closing door. The inside knob is always unlocked providing emergency exit.


G 3867



Patio Lock

Both levers locked or unlocked by push button inside. Closing door does not release button.


G 3863



Passage/Hall/Closet

Either knob operates latch bolt at all times.


G 3868



Communicating Lock

Both levers locked or unlocked by key in either lever. Turning key locks or unlocks its own lever independently.

G 3864



Store room/Hotel room

Outside knob unlocked only while key is inserted and turned. Pull key locked. Inside knob always free providing emergency exit.


G 3869



Exit Lock

Outside lever rigid. The inside lever is always unlocked providing emergency exit.

G 3865



Communication Lock

Both levers unlocked only while key is inserted and turned. Pull key locked.

Stock Code	Packing	Weight
G 3861	30 pcs	20 kgs
G 3862	30 pcs	19 kgs
G 3863	30 pcs	19 kgs
G 3864	30 pcs	20 kgs
G 3865	30 pcs	17 kgs
G 3866	30 pcs	20 kgs
G 3867	30 pcs	19 kgs
G 3868	30 pcs	21 kgs
G 3869	30 pcs	18 kgs



Meets underwriter's laboratories criteria. Specially designed for Standard Duty Certified to ANSI/BHMA A 156.2:2003 Sirim approval, Grade 3. Exceeds 200,000 cycles. Certification No: PC000359

Packing - Box pack